Aspirador – *Suction pump*
AI-78

ORDISI

المنارة

Aspirador gástrico intermitente modelo AI-78
Gastric-Intermittent suction pump mod.AI-78

Conectores rápidos y válvula de seguridad
Connectors and safety valve

Aspirador para drenaje gástrico, de aspiración continuo/intermitente, con selector de vacío prefijado a 90/120 mmHg y mandos reguladores de los ciclos de paro y puesta en marcha. El aspirador modelo AI-78, dispone de un sistema de aspiración completamente silencioso y libre de engrases, siendo estos factores óptimos para la utilización en UVI, UCI y salas.

Surgical aspirator for digestive drainage, intermittent or continuous, with prefixed vacuum selector to 90/120 mmHg. and regulators controls for the start/stop cycles. The aspirator model AI-78 has an extremely quiet aspiration system which requires no lubrication. These factors are optimum for the utilization of this equipment in UVI , UCI and rooms.

Panel de mandos con selector de continuos intermitentes
Control panel with continuous or intermittent selector

CARACTERÍSTICAS TÉCNICAS

Chasis:	Metálico, pintado al fuego
Motobomba:	De diafragma, sin engrase
Bomba:	Caudal 500 l/h (8.3 l/min)
Vacío :	Prefijado a 90/120 mmHg (11.99 / 15.99 kPa)
Programación:	Continuo / intermitente
ciclo marcha:	De 1 a 120 segundos
ciclo paro:	De 1 a 90 segundos
Frasco recolector:	Dos frascos de policarbonato de 3 litros
Tensión eléctrica:	230 V/ 50 Hz (otros bajo demanda)
Potencia:	18 VA
Medidas:	38 X 25 X 86 cm
Peso:	12 Kg aproximado
Normativa:	UNE EN 60601 / EN 61000 / UNE EN 10079

RECAMBIOS OPCIONALES

FB-193A	Filtro bactericida (10/50 unidades)
FV010018	Frasco recolector de 3 litros (2 unidades)
FV010300	Frasco recolector de 3 litros, con tapón y conectores.

Asa de transporte, sujeta cables y tubos
Transport handle, cables and tubes hold up

TECHICAL DATA

Chassis:	*Metallic, fire painted*
Engine pump:	*With membrane, no lubrication*
Pump:	*Flow 500 l /h (8.3 l/min)*
Vacuum:	*Prefixed 90 / 120 mmHg (11.99 / 15.99 kPa)*
Programme:	*Continuous / intermittent*
Start cycle:	*From 1 to 120 seconds*
Stop cycle:	*From 1 to 90 seconds*
Collecting flask:	*Two flasks of 3 litres in polycarbonate*
Voltage:	*230 V / 50 Hz (under request)*
Power:	*18 VA*
Sizes:	*38 X 25 X 86 cm*
Weight:	*12 Kg approximate*
Norms:	*UNE EN 60601 / EN 61.000 / UNE EN ISO 10079*

OPTIONAL SPARES

FB-193A	*Bacteria filter (10/50 units)*
FV010018	*Collecting flask of 3 litres (2 units)*
FV010300	*Collecting flask of 3 litres, with top and connectors*

ORDISI
Tecnologia, 2, nau 7
08780, PALLEJA (Barcelona), SPAIN
Tel.: (+34) 93 334 01 12 - Fax: (+34) 93 440 25 64
www.ordisi.com - comercial@ordisi.com - export@ordisi.com

CE 0051 ESQ ISO 9001:2008 CSQ MED ISO 13485 IQNet

tel: 07711011137-07715553335
Emeil: info@almanara-iq.com
website : www.almanara-iq.com
المنارة
مكتب المنارة الزرقاء العلمي